

## Proxes T1R - Ultra High Performance

The Proxes T1R is an ultra-high performance radial tyre that supersedes the Proxes T1-S. The Proxes T1R has the exceptional resistance to aquaplaning of the Proxes T1-S with improved wear resistance, cornering & braking grip in wet & dry conditions, ride comfort, resistance to irregular wear & reduced tread noise. The Proxes T1R is designed to provide extra high levels of traction in all driving conditions.



FEATURES	BENEFITS
Directional pattern with deep, wide tread grooves.	Exceptional resistance to aquaplaning.
Newly developed silica tread compound with ultra-high molecular polymer.	Improved levels of wet road grip and wear resistance.
Rigid tread shoulder block / rib arrangement.	Improved dry cornering grip, improved resistance to irregular shoulder wear, reduced tread noise & improved braking grip.
Deeper depth on tread shoulders compared to the Proxes T1-S.	Longer tread life.

### ***DIMENSIONAL DATA***

TYRE SIZE & SERVICE DESCRIPTION	TREAD DEPTH (mm)	INFLATED DIM.		LOADED DIMENSION			TEST RIM (INCH)	REVS PER KM.	APPROVED RIM WIDTH CODES (INCH)
		O.D. (mm)	O.W. (mm)	STATIC RADIUS	STATIC WIDTH	DYNAMIC RADIUS			
275/30ZR20 97Y	8.2	675	270	319	294	328	9.5	485	9.0 - 10.0
255/35ZR20 97Y	8.2	686	258	323	281	333	9.0	478	8.5 - 10.0
245/35ZR20 95Y	8.2	680	244	321	266	330	8.5	482	8.0 - 9.5
275/30ZR19 96Y	8.2	650	270	307	294	316	9.5	504	9.0 - 10.0
265/30ZR19 93Y	8.2	645	266	305	290	313	9.5	508	9.0 - 10.0
275/35ZR19 100Y	8.2	675	270	316	294	328	9.5	485	9.0 - 11.0
245/35ZR19 93Y	8.2	656	244	309	266	318	8.5	500	8.0 - 9.5
235/35ZR19 91Y	8.2	648	242	306	264	315	8.5	505	8.0 - 9.5
255/40ZR19 96Y	8.2	685	258	320	281	333	9.0	478	8.5 - 10.0
245/40ZR19 98Y	8.2	678	247	318	269	329	8.5	484	8.0 - 9.5

## Proxes T1R - Ultra High Performance

### *DIMENSIONAL DATA*

TYRE SIZE & SERVICE DESCRIPTION	TREAD DEPTH (mm)	INFLATED DIM.		LOADED DIMENSION			TEST RIM (INCH)	REVS PER KM.	APPROVED RIM WIDTH CODES (INCH)
		O.D. (mm)	O.W. (mm)	STATIC RADIUS	STATIC WIDTH	DYNAMIC RADIUS			
275/35ZR18 99Y	8.2	649	271	303	295	315	9.5	505	9.0 - 11.0
265/35ZR18 97Y	8.2	644	267	301	291	313	9.5	508	9.0 - 10.5
255/35ZR18 94Y	8.2	636	257	298	280	309	9.0	515	8.5 - 10.0
245/35ZR18 88Y	8.4	629	244	296	266	305	8.5	522	8.0 - 9.5
225/35ZR18 87Y	8.2	616	228	291	249	299	8.0	533	7.5 - 9.0
215/35ZR18 84W	8.2	608	219	287	239	295	7.5	540	7.0 - 8.5
245/40ZR18 97Y	8.2	651	277	304	266	316	8.5	504	8.0 - 9.5
235/40ZR18 95Y	8.2	643	242	301	264	312	8.5	510	8.0 - 9.5
225/40ZR18 92Y	8.2	637	231	299	252	309	8.0	515	7.5 - 9.0
255/45ZR18 99Y	8.2	686	250	318	273	333	8.5	478	8.0 - 9.5
245/45ZR18 96Y	8.4	676	242	314	264	328	8.0	485	7.5 - 9.0
235/50ZR18 101Y	8.4	689	243	319	265	334	7.5	477	6.5 - 8.5
245/35ZR17 87W	8.2	604	245	283	267	293	8.5	543	8.0 - 9.5
265/40ZR17 96Y	8.4	643	269	298	293	312	9.5	510	9.0 - 10.5
255/40ZR17 98Y	8.2	635	258	295	281	308	9.0	517	8.5 - 10.0
245/40ZR17 95Y	8.2	627	246	292	268	304	8.5	524	8.0 - 9.5
235/40ZR17 94Y	8.2	619	242	289	264	300	8.5	531	8.0 - 9.5
215/40ZR17 87W	8.2	604	222	283	242	293	7.5	543	7.0 - 8.0
205/40ZR17 84W	8.2	600	219	281	239	291	7.5	547	7.0 - 8.0
255/45ZR17 98Y	8.2	659	256	305	279	320	8.5	497	8.0 - 9.5
245/45ZR17 99Y	8.2	651	244	301	266	316	8.0	504	7.5 - 9.0
235/45ZR17 97Y	8.2	644	238	299	259	313	8.0	508	7.5 - 9.0
225/45ZR17 94Y	8.2	633	222	294	242	307	7.5	518	7.0 - 8.5
215/45ZR17 91W	8.2	626	211	292	230	304	7.0	524	7.0 - 8.0
215/50ZR17 91Y	8.4	644	225	299	245	313	7.0	508	6.0 - 7.5
205/50ZR17 93Y	8.4	635	212	295	231	308	6.5	517	5.5 - 7.5
225/40ZR16 85W	8.2	586	234	273	255	284	8.0	559	7.5 - 9.0
215/40ZR16 86W	8.2	578	222	270	242	281	7.5	566	7.0 - 8.5
245/45ZR16 94W	8.2	625	244	288	266	303	8.0	524	7.5 - 9.0
225/45ZR16 93W	8.2	608	227	282	247	295	7.5	540	7.0 - 8.0
205/45ZR16 87W	8.2	590	209	275	228	286	7.0	556	6.5 - 7.5
195/45R16 80V	8.2	583	195	272	213	283	6.5	562	6.0 - 7.5

## Proxes T1R - Ultra High Performance

### *DIMENSIONAL DATA*

TYRE SIZE & SERVICE DESCRIPTION	TREAD DEPTH (mm)	INFLATED DIM.		LOADED DIMENSION			TEST RIM (INCH)	REVS PER KM.	APPROVED RIM WIDTH CODES (INCH)	
		O.D. (mm)	O.W. (mm)	STATIC RADIUS	STATIC WIDTH	DYNAMIC RADIUS				
225/50ZR16 92W	8.4	628	233	290	254	305	7.0	522	6.0	- 8.0
205/50ZR16 87W	8.4	609	214	282	233	296	6.5	538	5.5	- 7.5
195/50R16 84V	8.4	600	199	279	217	291	6.0	547	5.5	- 7.0
185/50R16 81V	8.4	590	191	275	208	286	6.0	556	5.0	- 6.5
245/55ZR16 100W	8.4	671	254	306	277	326	7.5	488	7.0	- 8.5
225/55ZR16 99W	8.4	651	231	299	252	316	7.0	504	6.0	- 8.0
215/55ZR16 93W	8.4	639	223	294	243	310	7.0	513	6.0	- 7.5
205/55ZR16 91W	8.4	630	212	290	231	306	6.5	521	5.5	- 7.5
195/55R16 87V	8.4	618	200	286	218	300	6.0	531	5.5	- 7.0
225/50R15 91V	8.4	604	230	277	251	293	7.0	543	6.0	- 8.0
205/50R15 89V	8.4	587	211	271	230	285	6.5	558	5.5	- 7.5
195/50R15 82V	8.2	576	198	267	216	280	6.0	568	5.5	- 7.0
205/55R15 88V	8.4	605	214	278	233	294	6.5	541	5.5	- 7.5
195/55R15 85V	8.4	593	203	273	221	288	6.0	553	5.5	- 7.0
185/55R15 82V	8.4	584	192	270	209	283	6.0	562	5.0	- 6.5